

Smart Video Doorbell Total Solution



Communication



Protection



Recording



Major Benefits

- Answer your door from anywhere
- Real-time video call with your visitors
- Remote video monitoring, live view
- PIR (passive infrared) sensor motion detection
- Photo and video recording to the cloud


Hardware Features

- HD video
- Cellular phone quality real-time communication
- IP65 rating, dust- and watertight
- Loud speaker for hands free communication
- Active echo cancellation technology
- Works in extreme low temperatures
- Hardwired, maintenance free

Tecom provides cloud video doorbell total solution to our ODM customers. The system consists of 3 major parts : the video doorbell, the cloud server, and the smartphone App. In addition we provide Wi-Fi chime as a doorbell system accessory. Up to 4 Wi-Fi chimes can be paired with a single doorbell.

WE CUSTOMIZE FOR OUR ODM CUSTOMERS


1. Video doorbell industrial design.
2. iOS and Android App to easily integrate the doorbell features into your existing App.
3. We host the cloud server as a service.



Video Doorbell



Cloud Server



Smartphone App



Wi-Fi Chime

Cloud Smart Video Doorbell Total Solution



Easy Installation



Easy Setup



Total Mobility

D1021 Video Doorbell

Video	<ul style="list-style-type: none"> - Video : HD 720P - View angle: Horizontal 180 degree, Vertical 100 degree - Video codec: H.264 - Night vision: 2 IR LED, illuminates up to 5 meters, automated on/off control based on ambient light conditions - Video setting: brightness, contrast, saturation, gain
Audio	<ul style="list-style-type: none"> - Active echo cancellation - Audio codec: PCM, AAC - Cellula phone quality real-time communication
Connectivity	<ul style="list-style-type: none"> - Built-in 802.11 b/g/n
Motion detection	<ul style="list-style-type: none"> - Camera and/or PIR
Outdoor rating	<ul style="list-style-type: none"> - IP65
Power supply	<ul style="list-style-type: none"> - Support 10V 5W, 16V 10W and 16V 30W transformers
Temperature and humidity	<ul style="list-style-type: none"> - Operating temperature: -22 to +122°F - Operating humidity: 0% to 90% non-condensing
Dimensions	<ul style="list-style-type: none"> - Size: 140mm(H) x 50mm(W) x 25mm(D)
Weight	<ul style="list-style-type: none"> - <0.9 lbs

C1030 Wi-Fi Chime

Wi-Fi Connectivity	<ul style="list-style-type: none"> - 802.11n
Antenna	<ul style="list-style-type: none"> - Internal PCB Antenna, 2dBi gain
Power Supply	<ul style="list-style-type: none"> - 120V AC
Compatibility	<ul style="list-style-type: none"> - Works with D1021 doorbell and Cloud2Door Mobile App - 1 Doorbell can be paired with 4 Wi-Fi Chimes
Housing	<ul style="list-style-type: none"> - Plastic
Speaker	<ul style="list-style-type: none"> - 8Ω/0.5W
Status Indicator	<ul style="list-style-type: none"> - 2 LEDs
Ringtone	<ul style="list-style-type: none"> - 16 built-in melodies
Operating Environment	<ul style="list-style-type: none"> - Temperature 0°C to +40°C - Humidity 0% to 90%, non-condensing
Dimensions	<ul style="list-style-type: none"> - 78mm x 78mm x 37mm (without pins)